

How to measure floorspace for the purpose of the CIL

The RICS Code of Measuring Practice 6th edition definition of Gross Internal Area will be used in all instances. This is as follows:

Gross Internal Area (GIA) is the area of a building measured to the internal face of the perimeter walls at each floor level.

Including

- Areas occupied by internal walls and partitions
- Columns, piers, chimney breasts, stairwells, lift-wells, other internal projections, vertical ducts, and the like
- Atria and entrance halls, with clear height above, measured at base level only
- Internal open-sided balconies, walkways, and the like
- Structural, raked or stepped floors are to be treated as a level floor measured horizontally
- Horizontal floors, with permanent access, below structural, raked or stepped floors
- Corridors of a permanent essential nature (e.g. fire corridors, smoke lobbies)
- Mezzanine floor areas with permanent access
- Lift rooms, plant rooms, fuel stores, tank rooms which are housed in a covered structure of a permanent nature, whether or not above the main roof level
- Service accommodation such as toilets, toilet lobbies, bathrooms, showers, changing rooms, cleaners' rooms, and the like
- Projection rooms
- Voids over stairwells and lift shafts on upper floors
- Loading bays
- Areas with a headroom of less than 1.5m
- Pavement vaults
- Garages
- Conservatories

Excluding

- Perimeter wall thicknesses and external projections
- External open-sided balconies, covered ways and fire escapes
- Canopies
- Voids over or under structural, raked or stepped floors
- Greenhouses, garden stores, fuel stores, and the like in residential property